

CAT 50

TOOLING PACKAGE

Part #: TP-C50

$4,338.40 CAD

5 ER 32 Collet Chucks • 5 ER 20 Collet Chucks • 3 End Mill Holders
18-piece ER 32 Collet Set • 12-piece ER 20 Collet Set • ER 32 Wrench • ER 16 Wrench

Package includes:

Quantity	Part Number	Description
5	22291	CAT50 x ER 20 - 4"
5	22311	CAT50 x ER 32 - 4"
1	04210IS	ER20 x 12 piece, inch collet set
1	04212IS	ER32 x 18 piece, inch collet set
2	22945	CAT50 x SLN 1- 4"
1	22947	CAT50 x SLN 1-1/4 - 4.6"
1	04610	ER20 - A style wrench
1	04616	ER32 - E style wrench

Techniks Certified holders are inspected, tested, and measured for quality, accuracy, and balance.

A full lab report is included with each holder.

TECHNIKS TOOL GROUP

ER Collet Chucks Features

- Balanced to 25,000 RPM at G2.5
- T.I.R. 0.0001" measured from taper to collet pocket
- Taper ground to AT3 accuracy or better

End Mill Holders Features

- I.D. bore tolerance is H5
- Balanced to 15,000 RPM at G6.3
- Taper ground to AT3 for maximum spindle contact

E.M. PRECISE TOOL LTD.

216A Arvin Avenue, Stoney Creek, ON L8E 2L8

(905) 664-2644 | info@emprecise.com | www.emprecise.com



CAT 40

TOOLING PACKAGE

Part #: TP-C40

$3,142.15 CAD

4 ER 32 Collet Chucks • 2 ER 16 Collet Chucks • 6 End Mill Holders • Keyless Drill Chuck (w/ wrench)
18-piece ER 32 Collet Set • 10-piece ER 16 Collet Set • ER 32 Wrench • ER 16 Wrench

Package includes:

Quantity	Part Number	Description
4	22253	CAT 40 x ER 32 - 2.76"
2	22225	CAT 40 x ER 16 - 2.76"
1	04212IS	ER 32 x 18 piece collet set - Inch
1	04209IS	ER 16 x 10 piece collet set - Inch
1	22911	CAT 40 x SLN 1/4" - 3"
1	22915	CAT 40 x SLN 3/8" - 3"
1	22917	CAT 40 x SLN 1/2" - 3"
1	22919	CAT 40 x SLN 5/8" - 3"
1	22921	CAT 40 x SLN 3/4" - 3.5"
1	22925	CAT 40 x SLN 1" - 4"
1	22403	CAT 40 x SPU 1/2" - 4"
1	04609	ER 16 - A WRENCH
1	04616	ER 32 - E WRENCH

TECHNIKS TOOL GROUP

ER Collet Chucks Features

- Balanced to 25,000 RPM at G2.5
- T.I.R. 0.0001" measured from taper to collet pocket
- Taper ground to AT3 accuracy or better

End Mill Holders Features

- I.D. bore tolerance is H5
- Balanced to 15,000 RPM at G6.3
- Taper ground to AT3 for maximum spindle contact

E.M. PRECISE TOOL LTD.

216A Arvin Avenue, Stoney Creek, ON L8E 2L8

(905) 664-2644 | info@emprecise.com | www.emprecise.com